

Ytelseserklæring

OLDROYD® Torvtaksplate		Oktober 2020 - Utgave 4 Fuktsperre Identifikasjonskode 2142
-------------------------------	--	---

1. Entydig identifikasjon for produktet:	OLDROYD® Torvtaksplate xxxx xxxx= dimensjon på produktet
2. Type-, part- eller serienummer eller annen form for angivelse som muliggjør identifisering av byggevaren i samsvar med artikkel 11 nr. 4:	Se CE merking på produkt
3. Produsentens tilsiktede bruksområde for byggevaren, i samsvar med den relevante harmoniserte tekniske spesifikasjonen:	OLDROYD® Torvtaksplate er en grønnfarget fuktsperre til bruk mellom torv og underlagspapp.
4. Navn, registrert varemerke og kontaktadresse til produsenten i henhold til artikkel 11 nr. 5:	Oldroyd AS, Isdammen 25, N-3962 Stathelle
5. Navn og kontaktadresse til godkjent representant hvis mandat omfatter oppgavene angitt i artikkel 12 nr. 2:	Ikke relevant
6. Det eller de systemer for vurdering og kontroll av byggevarens ytelse, som fastsatt i vedlegg V:	2+
7. Dersom ytelseserklæringen gjelder en byggevare som omfattes av en harmonisert standard:	SP Technical Research Institute of Sweden, 0402-CPD-45 59 01
8. Dersom ytelseserklæringen gjelder en byggevare som det er utstedt en europeisk teknisk vurdering for:	Ikke relevant

Ytelseserklæring

OLDROYD® Torvtaksplate

Oktober 2020 - Utgave 4

Fuktsperre

Identifikasjonskode 2142

9. Angitte ytelser		
Egenskaper	Ytelse ¹⁾	Harmonisert teknisk spesifikasjon
Brannegenskaper	Uklassifisert	EN 13967:2012 Type V, ZA.1 og ZA.2 klasse 2+
Vanntetthet	Bestått	
Rivestyrke	> 300/ 200N	
Skjøtestyrke	NPD	
Slagstyrke	> 350 mm	
Strekstyrke	> 300 N/50 mm	
Motstand mot statisk last	> 200 N	
Farlige kjemikalier	Ingen (REACH, SVHC-listen)	
Holdbarhet:		
- Vanntetthet etter kunstig aldring	Bestått	
- Vanntetthet etter aldring med kjemikalier	Bestått	

1) Hvis ikke annet er oppgitt så gjelder verdiene for begge retninger av produktet hvor dette er relevant.

10. Ytelsen for varen som angitt i punkt 1 er i samsvar med ytelsen angitt i punkt 9. Denne ytelseserklæringen er utstedt på eget ansvar av Oldroyd AS, som angitt i punkt 4.

Undertegnet for og på vegne av Oldroyd AS:

Sted og dato	Navn og stilling	Underskrift
Stathelle 01.10.2020	Linda A. Celin / Daglig leder	

Declaration of Performance

OLDROYD® Torvtaksplate	October 2020 - Issue 4
	Moisture Barrier
	Identification Code 2142

1. Unique identification of the product.	OLDROYD® Torvtaksplate xxxx xxxx = dimension of product
2. The type, part- or serial number or other form of specification that enables the identification of the construction product in accordance with Article 11.4:	See CE label on product.
3. Manufacturer's intended use for the construction product, in accordance with the relevant harmonized technical specification:	OLDROYD® Torvtaksplate is a green-coloured moisture barrier for use in turf roof constructions.
4. Name, registered trademark and contact address of the manufacturer pursuant to Article 11. 5:	Oldroyd AS, Isdammen 25, N-3962 Stathelle
5. Name and contact address of authorized representative whose mandate covers the tasks specified in Article 12 no 2:	N.A.
6. Systems for evaluation and control of building hardware performance, as defined in Annex V:	2+
7. If performance statement applies construction materials covered by a harmonized standard:	SP Technical Research Institute of Sweden, 0402-CPD-45 59 01
8. If performance statement applies to construction materials where a European technical assessment has been issued:	N.A.

Declaration of Performance

OLDROYD® Torvtaksplate

October 2020 - Issue 4
Moisture Barrier
Identification Code 2142

9. Declared performance:		
Essential characteristics	Performance ¹⁾	Harmonised technical specification
Reaction to fire	Unclassified	EN 13967:2012 Type V, ZA.1 and ZA.2 class 2+
Water tightness	Pass	
Tear resistance	> 300/ 200N	
Joint strength	NPD	
Impact resistance	> 350 mm	
Tensile strength	> 300 N/50 mm	
Resistance to static load	> 200N	
Dangerous substances	None (REACH SVHC list)	
Durability		
- Water tightness after artificial aging	Pass	
- Water tightness after exposure against chemicals	Pass	

1) Unless otherwise specified as valid values for both directions of the product where relevant.

10. The performance of the product identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of Oldroyd AS, as identified in point 4.

Signed for and on behalf of Oldroyd AS:

Place and date	Managing Director	Signature
Stathelle 01.10.2020	Linda A. Celin	